




FIRE INSPIRED™

**CSA CERTIFIED-OUTDOOR USE ONLY
FOR COMMERCIAL AND RESIDENTIAL USE**

HEARTH PRODUCTS CONTROLS
2225 LYONS RD.
MIAMISBURG, OH 45342
TOLL FREE: 877.585.9800
PHONE: 937.436.9800
www.hpcfire.com



MATERIAL:
FIRE BOWL INSERT - 304 STAINLESS STEEL
BOWL - COPPER

PART NUMBER		WATER SCUPPER	IGNITION	STND BTU	TOR-BTU	VOLTAGE
TOR-	MESA32-EI	NO	ELECTRONIC	65K	90K	120VAC 24VAC
TOR-	MESA32W-EI	YES	ELECTRONIC	65K	90K	120VAC 24VAC 12VAC
TOR-	MESA32-MLFPK	NO	MATCH LIT	65K	65K	-
TOR-	MESA32W-MLFPK	YES	MATCH LIT	65K	65K	-


*FOR TORPEDO BURNERS ADD TOR-

Notes:


1. PROPER VENTING
 - Bowl to be raised above mounting surface
 - Minimum of 3/4" gap; Bowl to have a minimum of 6" diameter hole in bottom
2. GAS SUPPLY - FOR USE WITH FIXED PIPING SYSTEMS ONLY - NOT FOR USE WITH SMALL TANKS.
 - Natural Gas: Supply Pressure: Minimum: 3.5" W.C.; Maximum: 7.0" W.C.
 - LP Gas: Supply Pressure: Minimum: 8.0" W.C.; Maximum 11.0" W.C.

IMPORTANT: Ensure any flex line that may be used from the permanent main fuel supply to the product is rated to the stated max btu of the product and certified to ANSI Z21.75*CSA 6.27.


3. MODIFICATION OF PRODUCT WILL VOID ANY CERTIFICATION AND WARRANTY.
 4. FOLLOW ALL MANUFACTURER INSTALLATION INSTRUCTIONS AND LOCAL CODES.
 5. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS AS OF THE REVISION DATE.
 6. DO NOT SCALE DRAWING.
 7. THESE DRAWINGS ARE FOR SIZING AND PLANNING PURPOSES. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT. THE MANUFACTURER'S RESPONSIBLE FOR THE ACCURACY OF THE DRAWING.
 8. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info
- REFERENCE NUMBER 771-020



ISOMETRIC VIEW




ELECTRONIC IGNITION OPTION



MATCH LIT OPTION

ACCESS
DOOR

SPACERS
PROVIDED FOR
VENTILATION



MESA WITH EI FIRE PIT- FLAME SENSING WITH ELECTRONIC HOT SURFACE IGNITION
MESA WITH MATCH LIT FIRE PIT INSERT