

CSA CERTIFIED-OUTDOOR USE ONLY FOR COMMERCIAL AND RESIDENTIAL USE **HEARTH PRODUCTS CONTROLS** 2225 LYONS RD. MIAMISBURG, OH 45342


TOLL FREE: 877.585.9800 PHONE: 937.436.9800

18"

ELECTRONIC IGNITION OPTION

MATCH LIT OPTION

www.hpcfire.com




SPACERS

PROVIDED FOR

VENTILATION

PLAN VIEW MATERIAL: FIRE BOWL INSERT - 304 STAINLESS STEEL **BOWL - COPPER**

STND TOR-WATER PART NUMBER **IGNITION VOLTAGE SCUPPER** BTU BTU 120VAC TOR-SIER36-EI NO **ELECTRONIC** 65K 90K 24VAC 120VAC TOR-SIER36W-EI YES **ELECTRONIC** 65K 90K 24VAC 12VAC SIER36-MLFPK TOR-NO MATCH LIT 65K 65K



Notes:

1. PROPER VENTING

WATER SCUPPER

- Bowl to be raised above mounting surface
- Minimum of 3/4" gap; Bowl to have a minimum of 6" diameter hole in bottom
- 2. GAS SUPPLY FOR USE WITH FIXED PIPING SYSTEMS ONLY NOT FOR USE WITH SMALL TANKS.
 - Natural Gas: Supply Pressure: Minimum: 3.5" W.C.; Maximum: 7.0" W.C.
 - LP Gas: Supply Pressure: Minimum: 8.0" W.C.; Maximum 11.0" W.C.

IMPORTANT: Ensure any flex line that may be used from the permanent main fuel supply to the product is rated to the stated max btu of the product and certified to ANSI Z21.75*CSA 6.27.

- 3. MODIFCATION OF PRODUCT WILL VOID ANY CERTIFICATION AND WARRANTY.
- 4. FOLLOW ALL MANUFACTURER INSTALLATION INSTRUCTIONS AND LOCAL CODES.
- 5. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS AS OF THE REVISION DATE.
- DO NOT SCALE DRAWING.
- THESE DRAWINGS ARE FOR SIZING AND PLANNING PURPOSES. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT. THE MANUFACTURER'S RESPONSIBLE FOR THE ACCURACY OF THE DRAWING.
- 8. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info **REFERENCE NUMBER 771-021**



SIERRA WITH EI FIRE PIT- FLAME SENSING WITH ELECTRONIC HOT SURFACE IGNITION SIFRRA WITH MATCH LIT FIRE PIT INSERT

REVISION DATE 10/15/2024

<u>6</u>

ACCESS

DOOR

SPACERS

PROVIDED FOR

VENTILATION