


CSA CERTIFIED-OUTDOOR USE ONLY FOR COMMERCIAL AND RESIDENTIAL USE



AVAILABLE IN:

- •120VAC OR 24VAC
- ON/OFF OR HI/LO

MATERIAL: 304 STAINLESS STEEL

HI/LO MODELS HAVE A 40% REDUCTION IN BTU ON LOW SETTING

| PART NUMBER | BTU | DIMENSION CHART | | |
|-----------------|------|-----------------|--------|--------------|
| | | PAN | BURNER | C (+/- 1/2") |
| TOR-25X8SSEI-L | 75K | 25" | 24" | 7-3/4 |
| TOR-37X8SSEI-L | 115K | 37" | 36" | 7-3/4 |
| TOR-49X8SSEI-L | 150K | 49" | 48" | 7-3/4 |
| TOR-61X8SSEI-L | 175K | 61" | 60" | 7-3/4 |
| TOR-73X8SSEI-L | 200K | 73" | 72" | 7-3/4 |
| TOR-97X8SSEI-L | 300K | 97" | 96" | 7-3/4 |
| TOR-121X8SSEI-L | 300K | 121" | 120" | 7-3/4 |

NOTES:

1. PROPER VENTING

- ENCLOSURES:
 - For Fire Pit up to 200K BTU: Required minimum 2 vents, 18 sq.in. each on opposing sides.
 - For Fire Pit Inserts above 200K BTU: Required minimum 4 vents, 18 sq.in. each on opposing sides.
- BOWLS (Copper, concrete or metal)
 - For Fire Pit inserts up to 90K: Required minimum 2 vents, 9 sq.in. each on opposing sides.
 - Or bowl to be raised above mounting surface minimum of 3/4" gap; Bowl to have a minimum of 6" diameter hole in bottom.
- 2. GAS SUPPLY FOR USE WITH FIXED PIPING SYSTEMS ONLY NOT FOR USE WITH SMALL TANKS.
 - Natural Gas: Supply Pressure: Minimum: 3.5" W.C; Maximum: 7.0" W.C.
 - LP Gas: Supply Pressure: Minimum: 8" W.C.; Maximum: 11.0" W.C.

IMPORTANT: Ensure any flex line that may be used from the permanent main fuel supply to the product is rated to the stated max btu of the product and certified to ANSI Z21.75*CSA 6.27.


- 3. MODIFICATION OF PRODUCT WILL VOID ANY CERTIFICATION AND WARRANTY.
- 4. FOLLOW ALL MANUFACTURER'S INSTALLATION INSTRUCTIONS AND LOCAL CODES.
- 5. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS AS OF THE REVISION DATE.
- 6. DO NOT SCALE DRAWING.
- 7. THESE DRAWINGS ARE FOR SIZING AND PLANNING PURPOSES. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT. THE MANUFACTURER IS RESPONSIBLE FOR THE ACCURACY OF THE DRAWING.
- 8. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info REFERENCE NUMBER 771-043

ELECTRONIC IGNITION


EI LINEAR FLAME SENSING WITH ELECTRONIC HOT SURFACE IGNITION



HEARTH PRODUCTS CONTROLS



ISOMETRIC VIEW



FRONT ELEVATION

REVISION DATE 7/9/2024

771-043